

PRODUCT SPECIFICATIONS | REFLEX STEP

Applications

Suitable for garden, terrace, and courtyard surfacing, as well as for walkways, rest areas, and barbecue zones. Provides a safe, comfortable, and slip-resistant walking surface for outdoor applications.

Available colours



Key Features



slip-resistant surface



noise reduction



recycled



3 year warranty

General information

Density	Surface hardness	Reaction to fire classification
800 kg (+/-5%)	40-60 Shore A	Efi

Cleaning: The surface can be cleaned with mild detergent and water using a soft cloth or sponge. Abrasive cleaners, solvents, and strong acids or alkalis should be avoided.

Chemical resistance: The rubber tile shows good resistance to weak acids, alkalis, and mineral oils. Strong acids or alkalis, as well as prolonged oil exposure, may degrade its properties. Please test the material in the intended environment before chemical application.

Drainage capability: The product's porous structure and bottom drainage channels facilitate rainwater runoff and promote rapid surface drying.

100% recycled: The rubber granules are sourced entirely from recycled tires.

Item number	Description	Dimensions*	Thickness*	Weight	Critical fall height	units/ pallet	pallet dimensions (cm)	pallet weight
RF020404XX	ReFlex Step 2in1 rubber tile	40x40 cm	2 cm	2,47 kg	0,5 m	300	80x120x115	756 kg
		Raw material: SBR granulate (0,5-2 mm) + PU binder Certification type and reference number: EN1176-1, EN1177; EN 13501-12019, C-200320002796-1, MO-T182X-31735-2025/2						
RF030404XX		40x40 cm	3 cm	3,66 kg	1 m	210	80x120x120	784 kg
		Raw material: SBR granulate (0,5-2 mm) + PU binder Certification type and reference number: EN1176-1, EN1177; EN 13501-12019, C-200320002796-1, MO-T182X-31735-2025/2						
RFAG03040402	Reflex Step Grass rubber tile with 18 mm artificial grass wear layer	40x40 cm	3 cm	3,69 kg	0,7 m	210	80x120x120	845 kg
		Raw material: SBR granulate (1-3 mm) + PU binder + PP fabric-latex artificial grass Certification type and reference number: REACH; SHAHG1704923901						
RFF03040410	ReFlex Floor 2in1 rubber tile mix	40x40 cm	3 cm	4,39 kg	-	210	80x120x120	937 kg
		Raw material: SBR granulate (recycled technical and other rubber products) + PU binder						



Our products are certified by ÉMI-TÜV SÜD Ltd.



Manufactured in a facility operating under an ISO 9001:2015 quality management system.



REACH: The product complies with the requirements set out in Annex XVII of the EEA REACH Regulation.

*dimensional tolerance: ±1%

